

HAND TORQUE WRENCH ADJUSTABLE CLICK-TYPE TORQUE WRENCHES

Clicking type TT and NorTorque series torque wrenches are designed to be durable and long in lifetime. Quick and light adjustment over the entire scale and an adjustment lock allows the user to easily set the wrench and prevent accidental adjustment. In engineering the range of tools, Norbar has paid close attention to accuracy (+/-3%) which exceeds the requirements set by ISO6789-1:2017 standard for torque wrenches. Each torque wrench is delivered with a traceable calibration certificate and a robust carry case.

- Quick and light adjustment over the entire scale can quickly be achieved and with minimal effort in approximately ten complete turns
- All models feature a lock to prevent accidental adjustment of the set torque
- TTi20 and TTi50 have a change of direction with knob on top of ratchet, NorTorque 300 is reversible by pushthrough square drive
- I TTfth and NorTorqueFTH models have a female end
- I NorTorqueTH models have a 16mm spigot
- Comfortable and durable handle guarantees safe grip of tool



-	1	$\overline{}$	1	1
	lЗ	ŏ	ರ	ರ

Item	Model	Drive / Spigot / Female end fitting	Torque range Nm	Ratchet ø mm	Lenght mm	Weight kg		
Reversible Ratchet								
13833	TTi20	3/8"	4 - 20	30	232	0,5		
13844	TTi50	1/2"	10 - 50	30	329	0,7		
Push-through Ratchet								
130115	NorTorque 300	1/2"	60 - 300	52	587	1,4		
Female En	nd Fitting							
13840	TTfth20	9 x 12 mm	4 - 20	-	214	0,4		
13848	TTfth50	9 x 12 mm	10 - 50	-	310	0,6		
130131	NorTorque 60FTH	9 x 12 mm	12 - 60	-	319	0,6		
130133	NorTorque 100FTH	9 x 12 mm	20 - 100	-	360	0,7		
130135	NorTorque 200FTH	9 x 12 mm	40 - 200	-	437	0,8		
130136	NorTorque 200FTH	14 x 18 mm	40 - 200	-	446	0,9		
130137	NorTorque 300FTH	14 x 18 mm	60 - 300	-	566	1,2		
130138	NorTorque 340FTH	14 x 18 mm	60 - 340	-	658	1,3		
Spigot								
130161	NorTorque 60TH	16 mm	12 - 60	-	317	0,6		
130162	NorTorque 100TH	16 mm	20 - 100	-	357	0,7		
130163	NorTorque 200TH	16 mm	40 - 200	-	439	0,8		
130164	NorTorque 300TH	16 mm	60 - 300	-	564	1,1		