

PU SERIES

ELECTRIC PUMPS

- Quiet operation meets current OSHA noise regulations
- 2-speed function
- Start-up possible at full load
- Robust construction withstands heavy use even in demanding conditions
- High-quality components resist wear and ensure maintenance-free operation
- Available with 3- or 4-way valve
- Ideal for construction sites and industrial environments
- PEW03 remote control is supplied as an optional accessory



PU20M4N01C
Remote Control as Standard

MODELS EQUIPPED WITH SOLENOID DIRECTIONAL VALVE:

- 3.5-meter remote control as standard
- Solenoid directional valve available in 3- and 4-way versions



PEW03

Item	Power kW	Oil Capacity l	Output Flow Rate		Outlet Port	Current Draw amp	Dimensions LxPxK mm	Weight kg
			Stage 1 l/min	Stage 2 l/min				
230V Pumps								
PU20M4N01C	0,7	3,8*	2	0,4	3/8"-18NPTF	5	205 x 362 x 330	17,0
PE30M4U01D	0,37	3,8*	4,2	0,22	3/8"-18NPTF	4,5	301 x 419 x 485	28,5
PE40M4U02D	0,75	7,6*	4,2	0,46	3/8"-18NPTF	6	321 x 421 x 455	33,0
PE50M4U03D	1,12	11,4*	5,1	0,69	3/8"-18NPTF	8,5	325 x 421 x 502	41,5
PE50M4U05D	2,24	19,4*	6,3	1,22	3/8"-18NPTF	17	325 x 421 x 654	47,0
PE60M4U15D	2,24	60*	6,3	1,22	3/8"-18NPTF	17	419 x 531 x 879	76,0
380V Pumps								
PE60M4U06W	2,24	22,7*	6,3	1,33	3/8"-18NPTF	4,5	376 x 524 x 583	62,0
PEW03	Remote Control							
230V Pumps With Solenoid Valve [Only for Double Acting Cylinders]								
PE30S4U01D	0,37	3,8*	3,9	0,25	3/8"-18NPTF	4,5	301 x 419 x 485	33,5
PE40S4U02D	0,75	7,6*	4,2	0,49	3/8"-18NPTF	6	321 x 421 x 455	38,5
PE50S4U03D	1,12	11,4*	6,3	0,82	3/8"-18NPTF	8,5	325 x 421 x 502	46,6
PE60S4U05D	2,24	19,4*	7,1	1,48	3/8"-18NPTF	17	325 x 421 x 654	52,5

*) Also available with a larger oil reservoir



PE30M4N01D



PE30S4N01D