

## HAND TORQUE WRENCH BREAK-BACK MODELS

Breaking mechanism torque wrenches are engineered to reduce the risk of under and over tightening in production, service and repair industries. Wide range of tools are available in a torque range of 0.4-200 Nm in both preset and adjustable models. Adjustable models 25, 50 and 100 are supplied with a detachable ratchet head.

- Compact design allows easy access where space is restricted
- The 20° breaking angle mechanism eliminates the possibility of over-tightening
- Excellent repeatability
- Better than +/- 6% accuracy (ISO 6789:2017) for all models
- Available a wide selection of end fittings
- Preset wrenches are available as models with an electrical switch or a RF-transmitter/receiver for use in computer-controlled production



### ADJUSTABLE

Item	Model	Torque Range Nm	Lenght mm	Weight kg
<b>8 mm Spigot</b>				
050520	ATB 2.5	0,5 - 2,5	190	0,24
050500	ATB 5	1 - 5	220	0,29
050550	ATB 10	2 - 10	220	0,30
<b>9 x 12 mm Female End Fitting*</b>				
050527	ATB 2.5 G	0,5 - 2,5	192	0,27
050507	ATB 5 G	1 - 5	230	0,29
050557	ATB 10 G	2 - 10	230	0,30
<b>1/4" Drive</b>				
050636	ATB 25 D	5 - 25	345	1,11
<b>3/8" Drive</b>				
050638	ATB 25 A	5 - 25	345	1,12
050685	ATB 50	10 - 50	365	1,14
<b>1/2" Drive</b>				
050735	ATB 100	20 - 100	400	1,30

\*) ESD approved

### PRE-SET

Item	Model	Torque Range Nm	Lenght mm	Weight kg
<b>Locking Screw</b>				
011100	TBN 2	0,4 - 2	105	0,11
011200	TBN 10	1 - 10	105	0,13
<b>9 x 12 mm Female End Fitting</b>				
011110	TBN 2 G	0,4 - 2	133	0,13
011210	TBN 10 G	1 - 10	133	0,15
050010	TBN 25 G	5 - 25	265	0,41
050110	TBN 65 G	10 - 65	302	0,75
050210	TBN 135 G	27 - 135	408	1,03
<b>14 x 18 mm Female End Fitting</b>				
050310	TBN 200 G	40 - 200	520	1,40
<b>16 mm Spigot</b>				
050000	TBN 25	5 - 25	265	0,41
050100	TBN 65	10 - 65	302	0,75
050200	TBN 135	27 - 135	408	1,03
050300	TBN 200	40 - 200	520	1,40

