

CLECO CELLTEK BATTERY POWERED NUTRUNNER

The Cleco CellTek battery powered nutrunner series is the optimal nutrunner solution for safety-critical assembly work. The intelligent, sensor-controlled nutrunners are designed to withstand high usage, offering durability, lightweight construction, and ergonomic weight distribution.

The nutrunner can be connected to a control unit from up to 40 meters away, significantly facilitating its use in assembly work. The interface allows tightening values to be set, even without a separate control unit if needed.



ANGLE MODELS

Item	Torque range Nm	Free speed rpm	Weight kg	Lenght mm	Height mm	Drive
CTBAW153	3,6 - 15	1025	1,6	515	90	3/8" SQ
CTBAW213	5,2 - 21	735	1,6	515	90	3/8" SQ
CTBAW273	6,8 - 27	560	1,6	515	90	3/8" SQ
CTBAW383	10 - 38	395	1,65	526	90	3/8" SQ
CTBAW503	13 - 50	285	1,7	534	90	3/8" SQ
CTBAW653	17 - 65	220	1,8	543	90	3/8" SQ



PISTOL MODELS

Item	Torque range Nm	Free speed rpm	Weight kg	Lenght mm	Height mm	Drive
CTBPW05Q	1,1 - 4,9	3525	0,95	207	210	1/4" QC
CTBPW10Q	2,4 - 10	1600	1	207	210	1/4" QC
CTBPW15Q	3,4 - 14,4	1125	1	207	210	1/4" QC



LISÄVARUSTEET

Item	Description
T50-1000497	18 V/2.0 Ah battery
T50-1000498	18 V/5.0 Ah battery
T50-1000506	18 V rapid charger
T50-1000508	18 V 6-bay charger



Item	Compatible
T50-1102725	CTBPW05Q
T50-1102726	CTBPW10Q, CTBPW15Q
T50-3102254	CTBAW153, CTBAW213, CTBAW273
T50-3102255	CTBAW383
T50-3102256	CTBAW503
T50-3102257	CTBAW653

