

CLECO

PNEUMATIC ANGLE NUTRUNNERS – STALL WITH COLLAR REVERSE AND NON-REVERSIBLE

- Industry-leading torque accuracy and repeatability
- Indexable angle head for added versatility
- Lightweight and ergonomic design
- Easy to service and calibrate
- Durable grip material tested to withstand industrial chemicals
- Innovative and reliable air motor technology
- Durable and long-lasting bevel gears



Item	Max. torque Nm	Drive	Free speed rpm	Lenght mm	Head height mm	Side to center mm	Weight kg	Air consumption m³/min	Air inlet NPT
19 series									
19RAS03AM2	3,2	1/4" SQ	1 700	289,6	26,9	9,14	0,59	0,31	1/8"
19RAS04AH2	3,6	1/4" SQ	1 500	284,5	30,2	12,7	0,64	0,31	1/8"
19RAS05AM2	5,2	1/4" SQ	850	269,2	26,9	9,14	0,54	0,31	1/8"
19RAS06AH3	6,2	3/8" SQ	880	279,4	30,2	12,7	0,59	0,31	1/8"
55 & 75 series (reversible)									
55RNL-7T-4	55,6	1/2" SQ	490	408,9	41,4	18,3	2,78	2,00	1/2"
55RNL-4T-4	92	1/2" SQ	290	424,2	41,4	18,3	2,95	2,00	1/2"
55RNL-3T-4	135	1/2" SQ	195	424,2	41,4	18,3	2,95	2,00	1/2"
75RNL-4V-4	142	1/2" SQ	280	492,8	64,0	27,7	5,16	1,98	1/2"
55RNL-2T-4	176	1/2" SQ	145	424,2	41,4	18,3	2,95	2,00	1/2"
75RNL-3V-4	210	1/2" SQ	190	492,8	64,0	27,7	5,16	1,98	1/2"
75RNL-2V-4	278	1/2" SQ	140	492,8	63,5	27,7	5,16	1,98	1/2"
75RNL-3X-6	330	3/4" SQ	120	510,5	69,9	36,6	5,95	1,98	1/2"
75RNL-2X-6	440	3/4" SQ	90	510,5	69,9	36,6	5,95	1,98	1/2"
55 & 75 series (non-reversible)									
55NL-3T-4	149	1/2" SQ	290	424,2	50,0	22,4	2,89	2,00	1/2"
55NL-2T-4	190	1/2" SQ	210	424,2	50,0	22,4	2,89	2,00	1/2"



19RAS



55RNL