

CLECO

PNEUMATIC INLINE NUTRUNNERS – CLUTCH WITH REVERSE

- Durable Clecomatic Clutch delivers best-in-class torque repeatability and long calibration cycle
- Lightweight and ergonomic design
- External torque control – easy to service and calibrate
- Durable grip material tested to withstand industrial chemicals
- Innovative and reliable air motor technology
- 55 series models include a reaction arm



Item	Torque range Nm	Free speed rpm	Length mm	Weight kg	Drive	Air consumption m³/min	Air inlet NPT
19 series (Push-To-Start, Push button reverse)							
19BPA02Q	0,6 - 2,1	2 300	236,2	0,64	1/4" QC	0,31	1/8"
19BPA03B	0,6 - 2,9	2 300	251,5	0,64	BIT & FINDER	0,31	1/8"
19BPA03Q	0,6 - 2,9	1 600	236,2	0,64	1/4" QC	0,31	1/8"
19BPA04B	1,1 - 4,5	1 600	251,5	0,64	BIT & FINDER	0,31	1/8"
19BPA04Q	1,1 - 4,5	920	231,1	0,59	1/4" QC	0,31	1/8"
19BPA05B	1,1 - 5,1	920	251,5	0,59	BIT & FINDER	0,31	1/8"
19BPA05Q	1,1 - 5,1	560	241,3	0,68	1/4" QC	0,31	1/8"
19BPA06B	1,1 - 5,1	560	251,5	0,68	BIT & FINDER	0,31	1/8"
19BPA06Q	1,1 - 5,1	220	241,3	0,68	1/4" QC	0,31	1/8"
19 series (Push-To-Start, Collar reverse)							
19SPA02B	0,6 - 2,1	2 800	246,4	0,64	BIT & FINDER	0,31	1/8"
19SPA02Q	0,6 - 2,1	2 800	231,1	0,64	1/4" QC	0,31	1/8"
19SPA03B	0,6 - 2,9	1 900	251,5	0,64	BIT & FINDER	0,31	1/8"
19SPA03Q	0,6 - 2,9	1 900	236,2	0,64	1/4" QC	0,31	1/8"
19SPA04B	1,1 - 4,5	1 100	246,4	0,59	BIT & FINDER	0,31	1/8"
19SPA04Q	1,1 - 4,5	1 100	231,1	0,59	1/4" QC	0,31	1/8"
19SPA05B	1,1 - 5,1	660	256,5	0,68	BIT & FINDER	0,31	1/8"
19SPA05Q	1,1 - 5,1	660	241,3	0,68	1/4" QC	0,31	1/8"
19SPA06Q	1,1 - 5,1	260	241,3	0,68	1/4" QC	0,31	1/8"
19 series (Lever Push-To-Start, Collar reverse)							
19SCA02Q	0,6 - 2,1	2 800	248,9	0,68	1/4" QC	0,31	1/8"
19SCA03Q	0,6 - 2,9	1 900	254,0	0,68	1/4" QC	0,31	1/8"
19SCA04Q	1,1 - 4,5	1 100	248,9	0,68	1/4" QC	0,31	1/8"
19SCA05Q	1,1 - 5,1	660	259,1	0,73	1/4" QC	0,31	1/8"
19SCA06Q	1,1 - 5,1	260	259,1	0,73	1/4" QC	0,31	1/8"
55 series (Push-To-Start, Collar reverse)							
55RNAL-3-4	34 - 69	370	408,9	2,95	1/2" SQ	1,56	1/2"
55RNAL-2-4	46 - 91	270	408,9	2,95	1/2" SQ	1,56	1/2"



55RNAL



19SCA



19SPA