

CLECO IMPACT WRENCHES

CV SERIES COMPOSITE BODY

- Powerful twin hammer mechanism
- Trigger with speed control
- Lightweight and ergonomically balanced
- Ideal for general industrial and maintenance applications



Item	Max. torque Nm	Max. opening torque Nm	Free speed rpm	Weight kg	Drive	Drive type	Air consumption m ³ /min	Air inlet size
CV-375P	560	690	8 000	1,3	3/8"	Pin hole	0,91	1/4"
CV-375R	560	690	8 000	1,3	3/8"	Retaining ring	0,91	1/4"
CV-500P	1 050	1 490	8 500	2,2	1/2"	Pin hole	1,15	1/4"
CV-500R	1 050	1 490	8 500	2,2	1/2"	Retaining ring	1,15	1/4"
CV-750P	1 760	2 030	5 500	3,7	3/4"	Pin hole	1,81	3/8"
CV-750P-8	1 760	2 030	5 500	3,9	1"	Pin hole	1,81	3/8"

CWC SERIES PREMIUM COMPOSITE BODY

- Triple heat-treated twin hammer mechanism
- Trigger with speed control
- User-friendly one-handed direction switch
- Ideal for demanding industrial and high-speed production applications



Item	Max. torque Nm	Max. opening torque Nm	Free speed rpm	Weight kg	Drive	Drive type	Air consumption m ³ /min	Air inlet size
CWC-250QC	65	100	13 000	0,9	1/4"	Quick change	0,55	1/4"
CWC-250R	65	100	13 000	0,9	1/4"	Retaining ring	0,55	1/4"
CWC-375P	610	745	10 000	1,3	3/8"	Pin hole	1,06	1/4"
CWC-375R	610	745	10 000	1,3	3/8"	Retaining ring	1,06	1/4"
CWC-375R-4	610	745	10 000	1,3	1/2"	Retaining ring	1,06	1/4"
CWC-500P	1 085	1600	8 000	2	1/2"	Pin hole	1,15	1/4"
CWC-500R	1 085	1600	8 000	2	1/2"	Retaining ring	1,15	1/4"
CWC-750P	1 890	2440	6 500	3,5	3/4"	Pin hole	1,95	3/8"

CWM SERIES METAL BODY

- Triple heat-treated twin hammer mechanism
- Trigger with speed control
- Durable full metal housing
- Ideal for demanding industrial use and harsh conditions



Item	Max. torque Nm	Max. opening torque Nm	Free speed rpm	Weight kg	Drive	Drive type	Air consumption m ³ /min	Air inlet size
CWM-375P	450	610	12 000	1,5	3/8"	Pin hole	0,76	1/4"
CWM-375R	450	610	12 000	1,5	3/8"	Retaining ring	0,76	1/4"
CWM-500P	1 200	1 620	9 000	2,6	1/2"	Pin hole	1,13	1/4"
CWM-500R	1 200	1 620	9 000	2,6	1/2"	Retaining ring	1,13	1/4"
CWM-750P	2 330	2 330	6 000	4,7	3/4"	Pin hole	1,53	1/4"