

# TTT MEASUREMENT DEVICE

The TTT measurement device offers 3 transducer inputs, rather than 2. This will be particularly ideal for customers using the TTT with the TWL1500 loader and full compliment of three FMT Transducers. Any transducer from Norbar's 'SMART' range and most mV/V calibrated transducers from Norbar or other manufacturers can be connected to the TTT. All common measurement units for torque are included, in addition to which users can configure their own units to interface with non torque transducers.

Norbar TTT -näyttölaitteessa on kaikki vastaavat, edistyskelliset ominaisuudet kuin TST-mittauslaitteessa. TTT-näyttölaitteessa ei ole sisäistä anturia mutta sen sijaan siihen voi kytkeä samanaikaisesti kolme ulkoista anturia. Tämä mahdollistaa TTT:n käyttämisen kaikilla momenttialueilla.

- | 'SMART' intelligence for transducer recognition.
- | Up to 12 target values can be set
- | Limit detection with low, pass and fail indication
- | Resolution 5 digits for all Norbar transducers
- | All common measurement units for torque are included
- | RS-232-C serial data interface for connection to a printer or PC
- | Supplied in own robust carry case



Model	Item	Height mm	Width mm	Depth mm	Weight kg
TTT	43228	150	200	100	1

