

TECNA BALANCERS

Repetitive movements strain and burden the body, even if the tool is light. With TECNA balancers, repetitive strain can be reduced, thus enhancing the user's endurance and efficiency. Balancers reduce tool impacts and extend their service life.

- | Balancers widely available with a load range of 0.2 kg – 180 kg
- | Standard cable length up to 3 m
- | Cables available in three materials: Stainless steel, Nylon, and Pneumatic hose
- | Manufactured according to DIN 15112 directive
- | TECNA also offers alternative models for ESD (ES) and ATEX (AX) environments
- | New collection with Nylon cable
- | Available with a pneumatic hose in specific models (9310 - 9323)
- | Rubber cover available (9320 - 9323)

BALANCERS

Item			Variations			Load kg	Cable Length*	
Standard	Long	Automatic Locking	Nylon	ATEX	ESD		Standard	Long
Nylon Case								
9300	-	-	NY	-	-	0,2 - 0,5	1600	-
9301	-	-	NY	-	-	0,4 - 1	1600	-
9302	-	-	NY	-	-	1 - 2	1600	-
9303	-	-	NY	-	-	2 - 3	1600	-
Aluminium Case								
9310	-	-	NY	AX	ES	0,2 - 0,5	1600	-
9311	-	-	NY	AX	ES	0,4 - 1	1600	-
9312	-	-	NY	AX	ES	1 - 2	1600	-
9313	-	-	NY	AX	ES	2 - 3	1600	-
9320	-	-	NY	AX	ES	1 - 2,5	2000	-
9321	9336	9346	NY	AX	ES	2 - 4	2000	2500
9322	9337	9347	NY	AX	ES	4 - 6	2000	2500
9323	9338	9348	NY	AX	ES	6 - 8	2000	2500
9336L	-	9346L	NY	AX	ES	0,5 - 2	2500	-
9339	-	9349	NY	AX	ES	8 - 10	2500	-
9340	-	9350	NY	AX	ES	10 - 14	2500	-
Air Hose Cable								
9200	-	-	-	-	-	0,4 - 0,8	1350	-
9201	-	-	-	-	-	0,75 - 1,5	1350	-
9202	-	-	-	-	-	1,2 - 2,5	1350	-
9203	-	-	-	-	-	3 - 5	900	-

*) Extension cables available



9310



9300



9340AX



9310ES



9200

TECNA BALANCERS ZERO GRAVITY

Gravity-free models do not attempt to return to the starting position but hold the tool at the height where it was left.

Item	Variations			Load kg	Cable Length mm*					
	Standard	Long	Extra Long		G	ATEX	ESD	Standard	Long	Extra Long
9354	-	-	-	G	AX	ES	4 - 7	2000	-	-
9355	-	-	-	G	AX	ES	7 - 10	2000	-	-
9356	-	-	-	G	AX	ES	10 - 14	2000	-	-
9357	-	-	-	G	AX	ES	14 - 18	2000	-	-
9358	-	-	-	G	AX	ES	18 - 22	2000	-	-
9359	-	-	-	G	AX	ES	22 - 25	2000	-	-
9502	9521	-	-	-	AX	ES	20 - 30	2100	2700	-
9503	9522	-	-	-	AX	ES	30 - 40	2100	2700	-
9504	9523	-	-	-	AX	ES	40 - 50	2100	2700	-
9505	9524	-	-	-	AX	ES	50 - 60	2100	2700	-
9506	9525	-	-	-	AX	ES	60 - 70	2100	2700	-
9507	-	-	-	-	AX	ES	70 - 80	2100	-	-
9508	-	-	-	-	AX	ES	80 - 90	2100	-	-
9509	-	-	-	-	AX	ES	90 - 100	2100	-	-
9520	-	-	-	-	AX	ES	12 - 20	2700	-	-
9361	-	-	-	G	-	-	10 - 15	2000	-	-
9362	9401	9431	-	G	-	-	15 - 20	2000	2500	3000
9363	9432	-	-	G	-	-	20 - 25	2000	3000	-
9364	-	-	-	G	-	-	25 - 30	2000	-	-
9365	-	-	-	G	-	-	30 - 35	2000	-	-
9366	9434	-	-	G	-	-	35 - 45	2000	3000	-
9367	-	-	-	G	-	-	45 - 55	2000	-	-
9368	-	-	-	G	-	-	55 - 65	2000	-	-
9369	-	-	-	G	-	-	65 - 75	2000	-	-
9370	-	-	-	G	-	-	75 - 90	2000	-	-
9371	-	-	-	G	-	-	90 - 105	2000	-	-
9402	-	-	-	G	-	-	20 - 30	2500	-	-
9403	-	-	-	G	-	-	30 - 40	2500	-	-
9404	9435	-	-	G	-	-	40 - 50	2500	3000	-
9405	9436	-	-	G	-	-	50 - 60	2500	3000	-
9433	-	-	-	G	-	-	25 - 35	3000	-	-
9411	9441	-	-	G	-	-	60 - 70	2500	3000	-
9412	9442	-	-	G	-	-	70 - 80	2500	3000	-
9413	9443	-	-	G	-	-	80 - 90	2500	3000	-
9414	-	-	-	G	-	-	90 - 100	2500	-	-
9444	-	-	-	G	-	-	80 - 100	3000	-	-
9422	-	-	-	G	-	-	100 - 120	2500	-	-
9423	-	-	-	G	-	-	120 - 140	2500	-	-
9424	-	-	-	G	-	-	130 - 150	2500	-	-
9425	-	-	-	G	-	-	140 - 160	2500	-	-
9426	-	-	-	G	-	-	160 - 180	2500	-	-
9451	-	-	-	G	-	-	100 - 115	3000	-	-
9452	-	-	-	G	-	-	115 - 130	3000	-	-
9453	-	-	-	G	-	-	130 - 140	3000	-	-
9454	-	-	-	G	-	-	140 - 150	3000	-	-
9455	-	-	-	G	-	-	150 - 160	3000	-	-
9456	-	-	-	G	-	-	160 - 180	3000	-	-

*) Extension cables available



9354



9370G
G Models with rubber cover